

FB

(19) World Intellectual Property Organization  
International Bureau




(43) International Publication Date  
4 July 2002 (04.07.2002)

PCT

(10) International Publication Number  
**WO 02/052292 A1**

- (51) International Patent Classification<sup>7</sup>: **G01R 33/385**, 33/28 (72) Inventor: **HAM, Cornelis, L., G.**; Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (21) International Application Number: PCT/IB01/02466 (74) Agent: **BAKKER, Hendrik**; INTERNATIONAAL OCTROIBUREAU B.V., Prof. Holstlaan 6, NL-5656 AA Eindhoven (NL).
- (22) International Filing Date:  
10 December 2001 (10.12.2001) (81) Designated State (national): JP.
- (25) Filing Language: English (84) Designated States (regional): European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR).
- (26) Publication Language: English
- (30) Priority Data:  
00204807.2 22 December 2000 (22.12.2000) EP Published:  
— with international search report
- (71) Applicant: **KONINKLIJKE PHILIPS ELECTRONICS N.V.** [NL/NL]; Groenewoudseweg 1, NL-5621 BA Eindhoven (NL).  
*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

(54) Title: MEDICAL EXAMINATION APPARATUS PROVIDED WITH AT LEAST ONE MAGNET AND NOISE-ABSORBING MATERIAL



(57) Abstract: The invention relates to a medical examination apparatus (1) which includes at least one switchable magnet whose magnetic field can be applied to an organism to be examined in the operating condition. The invention notably relates to an examination apparatus (1) which includes a coil (3) that generates a magnetic field when current flows therethrough, and also includes a receiving space (2) that is provided in the interior of the coil so as to receive the organism to be examined, the examination apparatus (1) being mounted on the floor (5) and being constructed in such a manner that a noise-absorbing material (16) is provided in a

plane that is situated underneath the magnet (3).

WO 02/052292 A1

MEDICAL EXAMINATION APPARATUS PROVIDED WITH AT LEAST ONE MAGNET AND NOISE-ABSORB-  
ING MATERIAL

The invention relates to a medical examination apparatus as disclosed in the introductory part of claim 1, the magnetic field of which can be applied in operation to an organism to be examined, that is, notably a human or animal.

In examination apparatus of this kind there is customarily provided a space for  
5 receiving a patient, said receiving space being situated in the axial interior room of an outer coil. When current is applied to the coil, it produces a magnetic field that penetrates the patient who is arranged inside the coil and that is capable of creating a variety of effects that are used for imaging methods. In particular a plurality of magnet coils may be provided so as to generate first of all a static magnetic field, and secondly an alternating field that acts as a  
10 gradient field for the acquisition of position information, and finally an RF magnetic alternating field so as to cause resonance. Overall a plurality of magnetic fields are superposed. The RF magnetic alternating field is capable of exciting magnetic resonance that can be used for the re-orientation of nuclear spins. Such a spin excitation can be evaluated as a spatially resolved image of the organism examined, because it is contained completely in  
15 the inhomogeneous magnetic field and hence the resonance frequency varies in any position of the inhomogeneous field.

One or more magnets may be embedded in a cryostat so as to enable a temperature below the critical temperature for superconductivity. In order to generate an adequately strong magnetic field, it is necessary to keep the field generating coil in the  
20 superconducting state. The cryostat that is filled with liquid helium of a temperature of 4.2 °K is provided for this purpose.

The strong electromagnetic force (Lorenz force), being in the range of 100 kN, causes deformations of the coil that generates the gradient field. This results in a vibration that is transferred to the cryostat in which the gradient coil is mounted. This gives rise to a  
25 substantial amount of annoying noise, that is, in conjunction with switching operations for manipulating the gradient field whereby eddy currents are induced in the metal parts of the cryostat, and also in conjunctions with other sources of noise. The noise on the one hand is transferred as structure-borne noise directly to the floor, via parts of the apparatus such as the cryostats and its supports on the floor, and on the other hand as airborne noise to the

environment. Consequently, it is also transferred in the room in which the examination apparatus is installed. As a result, the partitioning of the room, notably the floor, also acts as a conductor for the noise. Therefore, neighboring rooms and rooms that are situated below the examination apparatus are also exposed to a significant noise load.

5                   It is an object of the invention to improve this situation.

This object is achieved in accordance with the invention by means of an examination apparatus as disclosed in the characterizing part of claim 1. Advantageous further embodiments are disclosed in the claims 2 to 7.

10                   The transfer of noise through an air space underneath the examination apparatus to the floor (for example, an intermediate ceiling) on which the examination apparatus is mounted can be significantly reduced by providing a noise-absorbing material in a plane that is situated underneath at least one switchable magnet. In addition to the damping of vibrations within the supports on the floor, a second form of damping is thus realized, which second form not only reduces the transfer of vibrations via fixed components but also  
15                   dampens the noise that is transferred through the air. The noise damping material can be used for reducing the acoustic load also without vibration damping in the supports.

Preferably, the noise insulation is provided between the supports on the floor, because at least one enclosure that elsewhere envelops the examination apparatus and already provides damping, for example a lining, can thus be dispensed with.

20                   It will be evident that a noise-absorbing material may be provided not only in the lower region but also in other peripheral regions of the examination apparatus, for example, also additionally within a lining.

When the noise-absorbing material is precut, for example, as a mat or a similar element, it can also be introduced into already installed examination apparatus at a later  
25                   stage.

Further advantages and details of the invention will become apparent from the following description of an embodiment of the invention that is shown in the accompanying drawing.

In the drawing:

30                   Fig. 1 is a diagrammatic front view of an examination apparatus that is mounted on the floor by way of feet,

Fig. 2 is a representation that is similar to that of Fig. 1 in which the transfer of noise is diagrammatically indicated, and

Fig. 3 is a representation that is similar to that of Fig. 1 in which a noise-absorbing material is provided underneath the magnet or magnets.

The examination apparatus 1 shown is a magnetic resonance tomography apparatus. It includes an examination space 2 in which, for example a patient to be examined  
5 can be introduced. In principle humans as well as animals can be examined. Other organisms, however, can also be examined.

The examination space 2 is enclosed by a magnet system 3 which includes at least one magnet that can be switched. The arrangement of the magnet coils or other magnets may vary in dependence on the configuration of the examination apparatus 1.

10 The magnet or magnets 3 are all embedded, for example, in a cryostat 4 in order to cool notably the coils to a temperature below a critical temperature for superconductivity. Switching operations, for example, during the generating of the magnetic gradient field, and any further noise sources in the examination apparatus 1 produce undesirable noise. Moreover, the cryostat 4 starts to vibrate. In order to prevent the transfer of  
15 such vibrations to the area of the floor 5, the support 6 via which the examination apparatus 1 is mounted on the floor 5 may be provided with vibration dampers 7 that are constructed, for example, as rubber elements and form part of the feet 6.

The present embodiment of the examination apparatus 1 is enclosed, that is, laterally outside and above the supports 6, by a lining 8 for optical enhancement as well as  
20 for noise insulation. As can be seen in Fig. 2, the lining 8 reduces the noise that is emitted by the cryostat 4, which noise is denoted by the wide arrows 9, in the space outside the lining 8 as indicated by the thin arrows 10. The noise load whereto the space 11 that surrounds the examination apparatus is exposed, therefore, is comparatively small because of the presence of the lining 8. Therefore, as is indicated by the dashed arrows 13, only a weak transfer of  
25 noise can take place from this outside space to a further room 12 that is situated below the room 11.

Vibrations of the floor 5, and hence also the transfer of the structure-borne noise by the cryostat via the supports 6, can be minimized by way of the vibration dampers 7. However, the transfer of noise in the lower region 14, below the arrangement of magnets 3, is  
30 impeded neither by the lining 8 nor by the vibration dampers 7, so that the noise 9 arising at that area is damped only by the intermediate ceiling 5; consequently, a comparatively large amount of noise is transferred, as indicated by the arrows 15, to the room 12 that is situated therebelow. The noise in the lower region 14, denoted by the arrows 9, is from approximately

10 dB to 20 dB higher than the level of the noise in the surrounding room outside the lining 8 as is indicated by the arrows 10.

Therefore, the major part of the transfer of noise to a room 12 that is situated therebelow takes place from the lower region 14 in which the lining 8 is absent. This transfer  
5 of noise is not essentially reduced when the supporting feet 6 are arranged closer to the center.

In order to reduce the noise load, notably for the room 12 that is situated below the examination apparatus 1, as is diagrammatically shown in Fig. 3 a noise-absorbing material 16 is provided in the region 14 underneath the magnet in accordance with the  
10 invention. The noise-absorbing material 16 may consist, for example, of a foam material that contains notably heavy components so as to realize effective damping. The foam material per se may be inhomogeneous and be provided with, for example additives of barium sulphate or other elements of higher density in comparison with the surrounding foam material. The use of, for example glass wool and/or rock wool is also possible.

15 The space 14 can either be filled completely with noise-absorbing material 16 or, as is shown in Fig. 3, there may be provided a mat that leaves regions that are clear from the examination apparatus 1. A space between the feet 6 and the lateral lining 8 may also be filled with a noise-absorbing material 16.

The noise-absorbing material 16 can be adapted, for example in that it consists  
20 of a unitary body that is precut so as to be adapted to the dimensions of the space 14, after which it is slid into said space. The foregoing can also be carried out in already installed examination apparatus 1.

It is also possible to provide loose noise protection material for adaptation to the shape of the space 14 which is then filled essentially by the introduction of individual  
25 pieces.




The noise protection material 16 notably reduces the transfer of noise to the room 12 that is situated below. Moreover, the amount of noise that emanates to the room 1 from the sides is also reduced, because this noise is damped.

The introduction of a noise-absorbing material 16 is also possible when the  
30 lining 8 also extends into the region 14 underneath the magnet 3. It is to be considered that the lining can provide effective protection against noise in this region only when it is closed overall. Therefore, in that case a noise-absorbing material is provided at least so as to enclose the supporting feet 6. Additionally, or alternatively, the entire space 14 can be filled with noise protection material 16 within a lining 8 thus pulled down.

## CLAIMS:

1. A medical examination apparatus (1) that includes at least one switchable magnet whose magnetic field can act on an organism to be examined in the operating condition, notably an examination apparatus (1) that includes a coil (3) which generates a magnetic field when a current flows therethrough and also includes a receiving space (2) for receiving the organism to be examined in the interior space of the coil (3), said examination apparatus (1) being mounted on the floor (5), characterized in that a noise-absorbing material (16) is provided in a plane that is situated underneath the magnet (3).
2. An examination apparatus as claimed in claim 1, characterized in that the examination apparatus (1) is mounted on the floor (5) by way of projecting feet (6), and that the noise-absorbing material (16) is provided in the intermediate space (14) between the feet (6).
3. An examination apparatus as claimed in one of the claims 1 or 2, characterized in that the examination apparatus (1) is a tomography apparatus that operates on the basis of magnetic resonance.
4. An examination apparatus as claimed in one of the claims 1 to 3, characterized in that the noise-absorbing material (16) consists at least partly of a foam material.
5. An examination apparatus as claimed in one of the claims 1 to 4, characterized in that the noise-absorbing material (16) is formed as a member that consists of a single piece.
6. An examination apparatus as claimed in claim 5, characterized in that the noise-absorbing material (16) is preformed so as to be adapted to a cavity (14) that is present underneath the examination apparatus (1).

7. An examination apparatus as claimed in one of the claims 1 to 6, characterized in that the noise-absorbing material (16) can be introduced into the intended space (14) in an installed examination apparatus (1).





## INTERNATIONAL SEARCH REPORT

ational Application No

.../IB 01/02466

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 G01R33/385 G01R33/28

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 7 G01R A61B

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ, WPI Data, INSPEC, MEDLINE

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 016 638 A (HSIEH CHI H) 21 May 1991 (1991-05-21) column 7, line 21 - line 39 ----	1,3
X	US 5 081 991 A (CHANCE BRITTON) 21 January 1992 (1992-01-21) column 6, line 41 - line 54 ----	1
X	DATABASE WPI Section PQ, Week 200104 Derwent Publications Ltd., London, GB; Class Q63, AN 2001-027218 XP002194917 -& JP 2000 230604 A (JEOL CO LTD), 22 August 2000 (2000-08-22) abstract ----- -/-	1,3

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

## \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

- \*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*Z\* document member of the same patent family

Date of the actual completion of the international search

4 April 2002

Date of mailing of the international search report

15/04/2002

Name and mailing address of the ISA  
European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Skalla, J

## INTERNATIONAL SEARCH REPORT

national Application No

J/IB 01/02466

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	PATENT ABSTRACTS OF JAPAN vol. 013, no. 402 (C-633), 6 September 1989 (1989-09-06) -& JP 01 145048 A (HITACHI MEDICAL CORP), 7 June 1989 (1989-06-07) abstract ----	1-3, 5
P, X	EP 1 085 336 A (GEN ELECTRIC) 21 March 2001 (2001-03-21) paragraph '0003! - paragraph '0007! ----	1-3
A	US 4 651 099 A (VINEGAR HAROLD J ET AL) 17 March 1987 (1987-03-17) column 5, line 15 - line 29 column 6, line 3 - line 7 ----	1, 4
A	US 5 617 026 A (YOSHINO HITOSHI ET AL) 1 April 1997 (1997-04-01) column 1, line 39 - line 48 -----	1

## INTERNATIONAL SEARCH REPORT

national Application No

PCT/IB 01/02466

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
US 5016638	A	21-05-1991	NONE		
US 5081991	A	21-01-1992	US	4981136 A	01-01-1991
			AU	633780 B2	04-02-1993
			AU	6579790 A	04-07-1991
			FR	2656210 A1	28-06-1991
			GB	2239523 A ,B	03-07-1991
			IE	902091 A1	03-07-1991
JP 2000230604	A	22-08-2000	NONE		
JP 01145048	A	07-06-1989	NONE		
EP 1085336	A	21-03-2001	EP	1085336 A2	21-03-2001
			JP	2001145611 A	29-05-2001
US 4651099	A	17-03-1987	US	RE33505 E	25-12-1990
US 5617026	A	01-04-1997	JP	7079952 A	28-03-1995
			JP	7275220 A	24-10-1995
			JP	8038442 A	13-02-1996
			JP	8038443 A	13-02-1996
			DE	4432747 A1	23-03-1995